

ICOM

IC-410PRO

80+ Channel UHF CB Transceiver



Noise Cancel
Microphone



5w/25w
Output Power



80+
Channels



CB
Commercial

**5 Year
Warranty**

1W/ 5W/ 25W OUTPUT POWER

5W output power (CB). Approved for 25W when using licensed private/commercial frequencies within 450-520MHz*

80+ CHANNELS

80 Channel UHF CB** plus up to 35 Private Channels.***

ACTIVE NOISE CANCEL MICROPHONE

This feature allows clear communication by reducing the surrounding noise, especially the unwanted low frequency noise received by the microphone.

CB/COMMERCIAL USE

The Compact and Rugged construction makes this product ideal for use in Commercial environments.



* ACMA Licensed users only

** 80 Channel UHF CB, 61-63 not present, reserved for future use.

*** Must be enabled using CS-410PRO software.

MADE IN JAPAN

■ Specifications

General

- Frequency range: 476.4250 MHz to 477.4125 MHz CB
450.0000 MHz to 520.0000 MHz LMR
- Number of conventional channels: 128 Ch
- Type of emission N: 8K50F3E (12.5kHz) CB
NW:8K50F3E / 16K0F3E (12.5kHz/25kHz) LMR
- Antenna impedance: 50 ohms nominal
- Operating temperature range -30 °C to + 60 °C
- Power supply voltage 13.8 V DC nominal
- Operating temperature range: -10°C to +60°C
- Power supply voltage: 13.8 or 27.6 V DC nominal
- Current drain (approx.) Receive stand-by 300 mA
Receive max audio 1200 mA
Transmit (25W) 7.0 A
Transmit (5W) 4.0 A
- Dimensions: W 150 x H 40 x D 117.5 mm
- Weight: 800 grams (approx)

Transmitter

- Rated output power: 1W/ 5W CB
1W/ 5W/ 25W (LMR)
- Modulation: Variable reactance frequency modulation
- Maximum permissible deviation ±2.5 kHz (Narrow)
±5.0 kHz (Wide)
- Frequency error: ± 2.50 ppm

Receiver

- Sensitivity: 0.25µV typ. @ 12 dB SINAD
- Audio power output 4.0 W typ. @ 5 % dist. With 4Ω

■ Applicable U.S. Military Specifications

Icom makes rugged products that have been tested and passed the following MIL-STD requirements and strict environmental standards.

Standard	MIL 810F	
	Method	Procedure
Low Pressure	500.4	I, II
High Temperature	501.4	I, II
Low Temperature	502.4	I, II
Temperature Shock	503.4	I
Solar Radiation	505.4	I
Rain	506.4	I, III
Humidity	507.4	—
Salt Fog	509.4	—
Dust	510.5	I
Vibration	514.5	I
Shock	516.5	I, IV

Also meets equivalent MIL-STD-810-C, -D and -E

■ Options

Microphone

- HM-211 — NOISE CANCELLING MICROPHONE (AS SUPPLIED)
- HM-152T — DTMF MICROPHONE
- SM-26 — DESKTOP MICROPHONE

Speakers

- SP-35 — EXTERNAL SPEAKER / 2M CABLE



■ Others

- CS-410PRO — #01 USER PROGRAMMING SOFTWARE
- OPC-1122U — USB CLONING CABLE
- OPC-1939 — D-SUB 15 PIN
- OPC-1194A — CORD DC 3M

■ Supplied Accessories

- Microphone HM-211
- Microphone hanger and screw set
- Microphone hanger cable
- DC power cable
- Mounting bracket

Icom Inc.

1-1-32 Kami-minami, Hirano-ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013

www.icom.co.jp/world

Count on us!

Icom, Icom Inc. and the Icom logo are registered trademarks of Icom Incorporated (Japan) in the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, Japan and/or other countries. All other trademarks are the properties of their respective holders.

Your local dealer: